An overview of our range of products

Experience quality on a completely new level, with the powerful products by Weiss:



COSMO® Adhesives

Durably firm joints

COSMO® CA (Cyanoacrylates) **COSMO® PU** (Polyurethane adhesives) **COSMO® CL** (Cleaning agents)

COSMO® SL (Dispersion adhesives)

COSMO® HD (Hybrid adhesives) **COSMO® EP** (Epoxy-resin adhesives)

COSMO® DS (Dispersion adhesives) **COSMO® SP** (Service products)

Fields of application

Windows and doors

Transportation / Marine engineering

Industry

Assembly

Dry construction Airtight bonding

Wood / Furniture industry

Container construction

Composite panels

Fire protection

Advertising industry

Do you have any questions?

Our Service Center Business area Adhesives:

+49 (0) 2773 / 815 - 255 +49 (0) 2773 / 815 - 274



COSMO® Composite panels

Unlimited possibilities for design

COSMO® Therm (heat-insulating) **COSMO® Silent** (sound insulating)

COSMO® Protect (burglar/penetration)

COSMO® Design (grooved)

COSMO® Tech (individual)

COSMO® Frame (frame widening)

Fields of application

Window and facade

Door construction

Industry

Automotive manufacturing

Trailer construction

Partition panel construction

Gate construction

Container construction

Energy conservation

Fire protection

Burglar resistance

Sound proofing

Do you have any questions?

Our Service Center Business Area Composite panels:

+49 (0) 2773 / 815 - 311

Our Service Center Business area Façade:

+49 (0) 5245 / 9241 - 21



PUDOL Cleaning and care agent

Cleanliness refreshes your senses

PUDOL SOFT

Mild cleaning agent for sensitive materials

PUDOL CARE

Maintenance product for high gloss and hygiene

PUDOL POWER

Powerful cleaning agent for extreme pollution

PUDOL FRESH

Cleaning agent for cleanliness and fresh air

Fields of application

Flooring

Sanitary installations

Clothing care

• Foodstuff industry

Household and gastronomy

Windows and glass

Dishwasher

Carpet and upholstery

Industry and workshop

Cars

Skin cleaning

Skin protection

Do you have any questions?

Our Service Center PUDOL:

1 +49 (0) 2743 / 9212 - 0



Weiss Chemie + Technik GmbH & Co. KG Hansastr. 2 D-35708 Haiger

Phone: +49 (0) 2773 / 815 - 0 Fax: +49 (0) 2773 / 815 - 200 E-mail: ks@weiss-chemie.de

Plant II Weiss Chemie + Technik GmbH & Co. KG Siemensstr. 8 D-33442 Herzebrock-Clarholz

Phone: +49 (0) 5245 / 9241 - 0 Fax: +49 (0) 02773-815-300 E-mail: se@weiss-chemie.de

PUDOI

Pudol Chemie GmbH & Co. KG Bahnhofstr. 2 D-57520 Niederdreisbach



A subsidiary of the Weiss Group

Phone: +49 (0) 2743 / 9212 - 0 Fax: +49 (0) 2743 / 9212 - 71 E-mail: info@pudol.de www.pudol.de

Cleanliness refreshes your senses

THE SAFE PUR CORNER ANGLE ADHESIVE

for aluminum window construction





INNOVATION MADE BY WEISS



H351-FREE

COSMO® PU-200.500 - The safe PUR adhesive



With our innovative corner angle adhesive COSMO® PU-200.500, we optimise aluminium corner angle bonding thanks to outstanding performance and no training being required.



HEALTH IN FOCUSLess hazard labeling, more safety.



TIME IS MONEY
Save time and money as diisocynate training is not required.



OUTSTANDING STRENGTH
Proven strength, as always with
our corner angle adhesives.



CURES VERY QUICKLY Time-saving efficiency.



COSMO® PU-200.500 is unique as a result of our innovative development work: It is exempt from the statutory training regulations for PUR adhesives – without compromising on performance. Experience maximum performance with COSMO® PU-200.500 – powerful, user-friendly and efficient.

MAXIMUM PERFORMANCE

COSMO® PU-200.500 - The high-performance PUR adhesive

SPECIAL PROPERTIES

- + ACHIEVES EXCELLENT ADHESION
- + VERY FAST CURING AND FUNCTIONAL STRENGTH
- + OPTIMAL PROCESSING TIME
- + CONTROLLED HARDENING
- + WEATHERPROOF AND UV RESISTANT
- + CAN BE OVER-COATED
- + SOLVENT-FREE
- + CAN SUBSEQUENTLY BE POWDER-COATED
- + CLASSIC AND INJECTION BONDING PROCEDURE
- + LOW LABELLING (FREE OF H351) & NO TRAINING REQUIRED



TOP PERFORMANCE LIKE OUR CLASSIC COSMO® PU-200.280

Product	COSMO® PU-200.500	COSMO® PU-200.280
Adhesive basis	Polyurethane	Polyurethane
Shore hardness	73D	85D
Film hardness	Tough-hard	Tough-hard
Viscosity +20°C	Low pasty	Low pasty
Pot life +20°C	approx. 23 min	approx. 60 min
Processing time in static mixer at +20°C	approx. 25 min	approx. 30 min
Functional strength +20°C	approx. 150-180 min	approx. 360 min
Special features	Low labelling (free of H351) No training required	ift-certified Classics over 30 years experience