COSMO[®] Corner Angle Adhesives

for aluminium windows and doors



COSMO® Corner Angle Adhesives

for aluminium windows and doors



Since 1995, renowned manufacturers of valuable aluminium elements have been relying on the reliability of our COSMO® Corner Angle Adhesives. Because of varied designs and other requirements, we developed further innovative variants of adhesive and successfully established them in the market over the years:

- + Functional strength optimised in time: from 20 minutes to 6 hours
- + Isocyanate Training: We are offering variants for which a diisocyanate safety training will not be required*
- + Hybrids: Hybrids provide safe bonding with simultaneous sealing and finishing of the mitre cut
- + Sustainability: With COSMO[®] PU-200.900 we are offering a bio-based variant (approx. 60% of bio-based raw materials)
- + Classic method and injection method: Many adhesives are suitable for the two methods**
- + French VOC-Emission Class A+: All variants meet Class A+



Frequently asked questions and answers referring to obligation to training on isocyanate: www.weiss-chemie.com/sicherheit-pu/

Side-I

00ml TAH 95ml



2-C-Adhesives	H351 free - No obligation to training on PUR		
Product	COSMO® PU-200.350	COSMO [®] HD-200.101	COSMO [®] HD-200.201
Adhesive basis	Polyurethane	STP-Hybrid	MS-Hybrid
Shore hardness	80D	63A	48A
Film hardness	Tough-hard	Elastic	Elastic
Pot life	approx. 30 min	approx. 30 min	approx. 40 min
Functional strength	approx. 180 min	approx. 210 min	approx. 270 min
Special Properties	H351(R40) free High UV colour stability	H351(R40) free High UV colour stability	H351(R40) free High UV colour stability
Packages	EM CARTRIDGE	-side albge CARTRIDGE	EM CARTRIDGE



Cleaning

Cleaning von aluminium- and powder-coated as well anodised surfaces.

Aluminium cleaner COSMO® CL-300.150 - non-dissolving

Removal of fresh adhesive residues, dust, marking pencil, rubber residues, fresh PU foam.



H351 free - No obligation to training on PUR **1-C-Adhesives** COSMO® HD-100.110 COSMO® HD-100.800 Product Adhesive basis STP-Hybrid STP-Hybrid Shore hardness 72A 74A Film hardness Elastic Elastic Skinning time approx. 9 min approx.9 min H351(R40) free H351(R40) free EC 1 **Special Properties** High UV cstability High UV stability Packages

		ì
	Classic PUR Corner A	١
COSMO® PU-200.280	COSMO® PU-200.310	
Polyurethane	Polyurethane	
85D	85D	
Tough-hard	Tough-hard	
approx. 60 min	approx. 20 min	
approx. 360 min	approx. 90 min	
ift-certified Classic product with more than 30 years of experience	Fast reaction time	
TANDEM CARTRIDGE 2 x 310 ml 2 x 190 ml 2 x 190 ml	TANDEM CARTRIDGE	








Anti-corrosion sealant COSMO® HD-100.411

Colour: grey (also available in white and black)

* Up to 24 August 2023, your employees who process PU adhesives must have received a diisocyanate safety training. This does not apply to COSMO® PU-200.350 and our hybrid adhesives.

** The user has to assess the suitability in the individual case. 1-C-adhesives are not suitable for the injection method.





To prevent blank cut aluminium edgesfrom corroding, they must actively be protected from air and moisture.

An overview of our range of products

Experience quality on a completely new level, with the powerful products by Weiss:



COSMO® Adhesives Durably firm bond joints

COSMO® CA (Cyanoacrylates) **COSMO® PU** (Polyurethane adhesives) **COSMO® CL** (Cleaning agents) **COSMO® SL** (Diffusion adhesives) **COSMO® HD** (Hybrid adhesives) **COSMO® EP** (Epoxy-resin adhesives) **COSMO® DS** (Dispersion adhesives) **COSMO® SP** (Service products)

Fields of application

- Windows and doors
- Transportation / Marine engineering
- Industry
- Assembly
- Dry construction
- Airtight bonding
- Wood / Furniture industry
- Container construction
- Composite panels
- Fire protection
- Advertising industry

Do you have any questions?

Our Service Center Adhesives Division:

+49 (0) 2773 / 815 - 255 +49 (0) 2773 / 815 - 274



COSMO® Composite Panels Unlimited possibilities for design

COSMO® Therm (heat-insulating) **COSMO® Silent** (sound insulating) **COSMO® Protect** (penetration-resistive) **COSMO® Design** (grooved) **COSMO® Tech** (individual) **COSMO® Frame** (frame widening)

Fields of application

- 🛨 Window and facade
- Door construction
- Industry
- Automotive manufacturing
- Trailer construction
- Partition panel construction
- Gate construction
- Container construction
- Energy conservation
- Fire protection
- Ð Burglar resistance
- Sound proofing

Do you have any questions?

Our Service Center Composite Panels Division: +49 (0) 2773 / 815 - 321

Our Service Center Façade Division: +49 (0) 5245 / 9241 - 21



PUDOL Cleaning and maintenance products Cleanliness refreshes your senses

PUDOL SOFT

Mild cleaning agent for sensitive materials **PUDOL CARE** Maintenance product for high gloss and hygiene

PUDOL POWER Powerful cleaning agent for extreme pollution

PUDOL FRESH Cleaning agent for cleanliness and fresh air

Fields of application

- 🛨 Sanitary area
- Clothing care
- 🛨 Food industry
- Household and gastronomy
- Windows and glass
- Dishwasher
- Carpet and upholstery
- Industry and workshop
- Cars
- Skin cleaning
- Skin protection

Do you have any questions?

Our Service Center PUDOL: +49 (0) 2743 / 9212 - 0



Plant I Weiss Chemie + Technik GmbH & Co. KG Hansastr. 2 D-35708 Haiger

Fax: +49 (0) 2773 / 815 - 200 E-mail: ks@weiss-chemie.de www.weiss-chemie.de

Plant II Weiss Chemie + Technik GmbH & Co. KG Siemensstr. 8 D-33442 Herzebrock-Clarholz

Phone: +49 (0) 5245 / 9241 - 0 Fax: +49 (0) 02773-815-300 E-mail: se@weiss-chemie.de

PUDOL

A subsidiary of the Weiss Group

Cleanliness refreshes your senses

Pudol Chemie GmbH & Co. KG Bahnhofstr. 2 D-57520 Niederdreisbach

Phone: +49 (0) 2743 / 9212 - 0 Fax: +49 (0) 2743 / 9212 - 71 E-mail: info@pudol.de www.pudol.de



Phone: +49 (0) 2773 / 815 - 0