SAFETY DATA SHEET

COSMO PU-205.120



(COSMOPUR 871 Hardener)

Section 1. Identification

GHS product identifier : COSMO PU-205.120

(COSMOPUR 871 Hardener)

Product code : Not available.

Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive.

Area of application : Professional applications.

Supplier's details : Weiss USA LLC

P.O. Box 509

USA, Monroe, NC 28111-0509

For information, contact the Product Safety Department

Telephone no.: (001) 704 282 4496 E-Mail: Stephen@weiss-usa.com

e-mail address of person responsible for this SDS

: Stephen@weiss-usa.com

Emergency telephone number (with hours of

operation)

: +1 872 5888271 (WIC)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: H315 SKIN IRRITATION - Category 2 H319 EYE IRRITATION - Category 2A

H334 RESPIRATORY SENSITIZATION - Category 1

H317 SKIN SENSITIZATION - Category 1

H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

(Respiratory tract irritation) - Category 3

H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)

(respiratory system) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity:

19.8%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity:

19.8%

GHS label elements

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 1/16

Section 2. Hazards identification

Hazard pictograms





Signal word

: Danger

Hazard statements

: H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

(respiratory system)

Precautionary statements

Prevention

: P280 - Wear protective gloves: 1 - 4 hours (breakthrough time): Recommended: Nitrile

gloves. Protective hand cream.. Wear eye or face protection. P284 - Wear respiratory protection: Recommended: Filter A P2.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe vapor.

P264 - Wash hands thoroughly after handling.

P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.

Response

: P314 - Get medical attention if you feel unwell.

P304 + P341 (OSHA) + P312 - IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

you leel ullwell.

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or

physician.

P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

identification

Ingredient name	Other names	%	CAS number
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	-	≥10 - ≤25	-
4,4'-Methylenediphenyl diisocyanate, oligomers 4,4'-methylenediphenyl diisocyanate		≥10 - ≤25 ≥10 - ≤21	25686-28-6 101-68-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 2/16

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 3/16

(COSMOPUR 871 Hardener)

Section 4. First aid measures

Skin contact

: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: In case of fire, use water spray (fog), foam, dry chemical or CO2.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Hydrogen cyanide (HCN).

Toxic gases

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Remark

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Not considered to be a product presenting a risk of explosion.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 4/16

Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 15 to 25°C (59 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version: 1

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-	ACGIH TLV (United States, 1/2013).
isocyanatobenzyl)phenyl isocyanate	Absorbed through skin.
	TWA: 0.02 ppm, (as Methyl isocyanate (-
	NCO))
4,4'-Methylenediphenyl diisocyanate, oligomers	ACGIH TLV (United States, 1/2013).
	Absorbed through skin.
	TWA: 0.02 ppm, (as Methyl isocyanate (-
	NCO))
4,4'-methylenediphenyl diisocyanate	ACGIH TLV (United States, 3/2019).
	TWA: 0.005 ppm 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 0.05 mg/m³ 10 hours.
	TWA: 0.005 ppm 10 hours.
	CEIL: 0.2 mg/m³ 10 minutes.
	CEIL: 0.02 ppm 10 minutes.
	OSHA PEL (United States, 5/2018).
	CEIL: 0.02 ppm
	CEIL: 0.2 mg/m³

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): Recommended: Nitrile gloves. Protective hand cream.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 6/16

(COSMOPUR 871 Hardener)

Section 8. Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Long-sleeved protective clothing.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Filter A P2

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Paste-like.]

Color : According to specification

Odor : Characteristic.
Odor threshold : Not available.
pH : Not applicable.
Melting point : Not available.
Boiling point : Not available.
Flash point : Not applicable.
Evaporation rate : Not applicable.

Flammability (solid, gas)
Lower and upper explosive

(flammable) limits

Not applicable.Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Density: ~ 1.55 g/cm³

Solubility : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Physical/chemical : VOC content: 0.39 (~6 g/l)

properties comments

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 7/16

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Hazardous reactions or instability may occur under certain conditions of storage or use. May react or be incompatible with water. Protect from moisture.

Hazardous polymerization may occur under certain conditions of storage or use. Strong

heat. (T>~260°C)

Conditions to avoid

: May react or be incompatible with water. Protect from moisture.

Incompatible materials

: Reactive or incompatible with the following materials: acids and alkalis. Incompatible materials: amines, alcohols, water.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-Methylenediphenyl diisocyanate, oligomers	LD50 Dermal	Rabbit	>9400 mg/kg	-
4,4'-methylenediphenyl	LD50 Oral LC50 Inhalation Dusts and mists	Rat Rat	>5000 mg/kg 0.368 mg/l	- 4 hours
diisocyanate	LD50 Dermal	Rabbit	>2000 mg/kg	
	LD50 Oral	Rat	9200 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-Methylenediphenyl diisocyanate, oligomers	Skin - Irritant	Rabbit	-	-	-
4,4'-methylenediphenyl diisocyanate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Irritant	Rabbit	-	-	-

Sensitization

Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
1 '	471 Bacterial Reverse Mutation Test	Subject: Bacteria	Negative

Conclusion/Summary

Carcinogenicity

: Not available.

Conclusion/Summary

: Not available.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version :1 8/16

Section 11. Toxicological information

Classification

Product/ingredient name	OSHA	IARC	NTP
4,4'-methylenediphenyl diisocyanate	-	3	-

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Category 3	Not applicable.	Respiratory tract irritation
4,4'-Methylenediphenyl diisocyanate, oligomers	Category 3	Not applicable.	Respiratory tract irritation
4,4'-methylenediphenyl diisocyanate	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Category 2	Inhalation	respiratory system
4,4'-Methylenediphenyl diisocyanate, oligomers 4,4'-methylenediphenyl diisocyanate	Category 2 Category 2		respiratory system Not determined

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 9/16

(COSMOPUR 871 Hardener)

Section 11. Toxicological information

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
COSMO PU-205.120 Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl	4654.6	3597.6	N/A	31.1	N/A
	N/A	N/A	N/A	11	N/A
isocyanate 4,4'-Methylenediphenyl diisocyanate, oligomers 4,4'-methylenediphenyl diisocyanate	N/A	N/A	N/A	11	N/A
	9200	2500	N/A	N/A	0.368

Section 12. Ecological information

Toxicity

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 10/16

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p- isocyanatobenzyl)phenyl isocyanate	EC50 >1640 mg/l	Algae	72 hours
	NOEC >10 mg/l Acute LC50 >1000 mg/l	Daphnia - Daphnia magma Fish	21 days 96 hours
4,4'-Methylenediphenyl diisocyanate, oligomers	EC50 >1640 mg/l	Algae	72 hours
	NOEC >10 mg/l Acute LC50 >1000 mg/l	Daphnia - Daphnia magma Fish	21 days 96 hours
4,4'-methylenediphenyl diisocyanate	EC50 1.5 mg/l	Algae	72 hours
	NOEC 1640 mg/l	Algae - Desmodesmus subspicatus	72 hours
	Acute LC50 >1000 mg/l	Fish - Brachydanio rerio	96 hours

Conclusion/Summary: Not available.

Persistence and degradability

Product/ingredient name	Test	Result		Result Dose		Inoculum
4,4'-methylenediphenyl diisocyanate	302C Inherent Biodegradability: Modified MITI Test (II)	0 % - 28 days		-		-
Product/ingredient name	Aquatic half-life	ic half-life Photolysis			Biodeg	radability
4,4'-methylenediphenyl diisocyanate	-		-		Not rea	dily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p- isocyanatobenzyl)phenyl isocyanate	-	200	low
4,4'-Methylenediphenyl diisocyanate, oligomers	8.56	200	low
4,4'-methylenediphenyl diisocyanate	4.51	200	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version :1 11/16

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	NA3082	Not regulated.	Not regulated.
UN proper shipping name	Hazardous waste, liquid, n.o.s. (4,4'-methylenediphenyl diisocyanate)	-	-
Transport hazard class(es)	9	-	-
Packing group	III	-	-
Environmental hazards	No.	No.	No.

Additional information

DOT Classification

: Reportable quantity 42119.5 lbs / 19122.2 kg [3259.1 gal / 12336.9 L]. The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

Limited quantity Yes.

Packaging instruction Exceptions: 155. Non-bulk: 203. Bulk: 241.

Special provisions IB3, T2, TP1

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version: 1 12/16

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: 4,4'-methylenediphenyl diisocyanate; Siloxanes and Silicones, di-Me, reaction products with silica

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

TSCA 8(c) calls for record of SAR: 4,4'-methylenediphenyl diisocyanate

United States inventory (TSCA 8b): Not determined.

Clean Water Act (CWA) 307: 4,4'-methylenediphenyl diisocyanate

Clean Water Act (CWA) 311: Phosphoric acid, solution

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A

RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory system) -

Category 2

Composition/information on ingredients

Name	%	Classification
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate	≥10 - ≤25	ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory system) (inhalation) - Category 2
4,4'-Methylenediphenyl diisocyanate, oligomers	≥10 - ≤25	ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 13/16

Section 15. Regulatory information

4,4'-methylenediphenyl diisocyanate	≥10 - ≤21	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory system) (inhalation) - Category 2 ACUTE TOXICITY (inhalation) - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
		EXT GOOTIE, - Gategory 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	4,4'-methylenediphenyl diisocyanate	101-68-8	≥10 - ≤21
Supplier notification	4,4'-methylenediphenyl diisocyanate	101-68-8	≥10 - ≤21

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: METHYLENE BISPHENYL ISOCYANATE;

DIPHENYLMETHANE DIISOCYANATE; MDI

New York : The following components are listed: Methylene diphenyl diisocyanate

New Jersey : The following components are listed: METHYLENE BISPHENYL ISOCYANATE;

BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-

Pennsylvania : The following components are listed: BENZENE, 1,1'-METHYLENEBIS

[4-ISOCYANATO-

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 14/16

(COSMOPUR 871 Hardener)

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2A, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373 (respiratory system)	Calculation method

History

Date of issue/Date of : 01/13/2020

revision

Date of previous issue : 01/13/2020

Version : 1

Prepared by : Chemical Check GmbH

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 15/16

(COSMOPUR 871 Hardener)

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 01/13/2020 Date of previous issue : 01/13/2020 Version : 1 16/16