



COSMO® CL-300.110

*** COSMOFEN 5

PVC cleaner, strongly dissolving

Examples for Application

- PVC window construction as polishing and smoothing agent
- Furniture and advertising material industry for smoothing of occurred scratches, cracks, grit marks, etc. on not transparent PVC hard, PS, ABS, PMMA(acryl)

Special Properties

- Strongly dissolves PVC hard
- Fast drying

Technical Data

Basis	Mixed mono carbonic acid ester and aliphatic ketones
Density as per EN 542 at +20 °C	approx. 0.84 g/cm ³
Processing temperatures	from +5 °C to +30 °C

Instructions for use

Acclimatise the product before the application.

Always check the surfaces to be cleaned for compatibility!

Due to the hygroscopic effect of dissolved PVC, dissolving agents are only allowed to be used under dry climatic conditions.

At first, the surfaces to be repaired are cleaned with COSMO® CL-300.140 SPECIAL (non-dissolving) to remove possibly existing dust or other surface pollution.

If the scratches are deep, the surface is to be ground using an eccentric grinder (grit class 400). After that, the grinding dust is removed from the surface with COSMO® CL-300.140 SPECIAL.

The surface is then smoothed using a lint-free, not marking, wrinkle-free cellulose cloth in one direction each.

For lighter cleaning works, COSMO® CL-300.120 (slightly dissolving) is available.

Important instructions

Only instructed personnel in specialist firms are allowed to use the product!

Our user instructions, processing guidelines, product- and performance data, and other technical statements are only general directives; they describe only the condition of our products (values, determination of values on the date of completion) and the performances do not represent a warranty in the sense of § 443 BGB. **Because of the wide variety of applications of the individual product and the relevant special conditions (e. g. processing parameters, material characteristics, etc.), it is up to the user to test it itself;** our free expert advice for application provided in speech, writing, and as test is nonbinding.

Please, also consider the Safety Data Sheet!

Storage

Store the hermetically closed original trading units, in a dry place at temperatures of +15 °C to +25 °C no direct sun radiation.

While transported within the usual transport times, the product may be exposed to temperatures from -30 °C to +35 °C.

Storage life in unopened original packaging: 24 Months.

Packaging

1 000 ml metal bottle

10 l metal canister

Accessories

COSMO® SP-870.100 - Pulp cleaning cloth

COSMO® SP-810.120 - Saving humidifier/safety dispenser

