



# COSMO® CL-300.120

\*\*\* COSMOFEN 10

## PVC cleaner, slightly dissolving

### Examples for Application

- Plastic window construction for preparation of bonding and removal of marks on profiles made of PVC hard white
- Cleaning of several, not transparent thermo-plastic and duroplast plastic material in the different industrial applications

### Special Properties

- Slightly dissolves PVC hard
- No impairment on weather resistance of cleaned PVC profiles
- Fast drying

### Technical Data

<b>Basis</b>	Mixed mono carbonic acid ester
<b>Density</b> as per EN 542 at +20 °C	approx. 0.90 g/cm <sup>3</sup>
<b>Processing temperatures</b>	from +5 °C to +30 °C

### Instructions for use

Acclimatise the product before the application.

Always check the surfaces to be cleaned for compatibility!

Due to the hygroscopic effect of dissolved PVC, dissolving agents are only allowed to be used under dry climatic conditions.

The dry, dust-free material surface is cleaned using lint-free and non-marking rags made of pulp or cotton.

If the surfaces are very dusty, it will be required to pre-clean them with COSMO® CL-300.140 SPECIAL (non-dissolving).

Usually, it will be sufficient to clean the surface one time only.

If it is more strongly polluted, the cleaning process can be repeated after the material surface has been cured.

For polishing and repair works, the COSMO® CL-300.110 (strongly dissolving) is available.

### Important instructions

Only instructed personnel in specialist firms are allowed to use the product!

Our user instructions, processing guidelines, product- and performance data, and other technical statements are only general directives; they describe only the condition of our products (values, determination of values on the date of completion) and the performances do not represent a warranty in the sense of § 443 BGB. **Because of the wide variety of applications of the individual product and the relevant special conditions (e. g. processing parameters, material characteristics, etc.), it is up to the user to test it itself;** our free expert advice for application provided in speech, writing, and as test is nonbinding.

*Please, also consider the Safety Data Sheet!*

### Storage

Store the hermetically closed original trading units, in a dry place at temperatures of +15 °C to +25 °C no direct sun radiation.

While transported within the usual transport times, the product may be exposed to temperatures from -30 °C to +35 °C.

Storage life in unopened original packaging: 24 Months.

### Packaging

- 1 000 ml metal bottle
- 10 l metal canister
- 30 l metal canister
- 200 l metal bung hole drum

### Accessories

- COSMO® SP-870.100 - Pulp cleaning cloth
- COSMO® SP-810.120 - Saving humidifier/safety dispenser

