



## Special cleaner

### Examples for Application

- Cleaning of lacquered surfaces in the plastic and metal processing industry
- Removal of not cured residues of different adhesive systems
- Cleaning of several, not transparent thermo-plastic and duroplast plastic material in the different industrial applications
- Window and door construction for cleaning of the powder-coated and anodized aluminium and PUR sections
- Cleaning of PVC hard white and aluminium-anodized surfaces, as well as for cleaning other smooth, mainly plastic surfaces
- Removal of dust, adhesive residues of the protective film, marking pencil, rubber residues, fresh PUR foam and fresh sealant residues, as well as tar / bitumen spots

### Special Properties

- Non-flammable\*
- Non-dissolving
- Mild to surfaces
- Mild odour during processing

### Technical Data

<b>Basis</b>	Mixed aliphatic hydrocarbons
<b>Density</b> as per EN 542 at +20 °C	approx. 0.79 g/cm <sup>3</sup>
<b>Processing temperatures</b>	from +5 °C to +30 °C

### Instructions for use

Acclimatise the product before the application.

Always check the surfaces to be cleaned for compatibility!

The dry, dust-free material surface is cleaned using lint-free and non-marking rags made of pulp or cotton.

If, during the cleaning process, colouring pigments can be detected in the cleaning cloth, this can also indicate that the powder coating has not cured sufficiently. In this case, also the powder coating expert should be asked.

### Important instructions

\*No GHS02 „Flame“- labelling required.

The cleaner is not suitable for the use on decorative films and transparent plastics!

Only instructed personnel in specialist firms are allowed to use the product!

Our user instructions, processing guidelines, product- and performance data, and other technical statements are only general directives; they describe only the condition of our products (values, determination of values on the date of completion) and the performances do not represent a warranty in the sense of § 443 BGB. **Because of the wide variety of applications of the individual product and the relevant special conditions (e. g. processing parameters, material characteristics, etc.), it is up to the user to test it itself;** our free expert advice for application provided in speech, writing, and as test is nonbinding.

If used for pre-cleaning in connection with following bonding, sealing or lacquer coating the cleaning agent must have flashed off completely without residues, wipe it dry using a dry cloth, if necessary.

*Please, also consider the Safety Data Sheet!*

### Storage

Store the hermetically closed original trading units, in a dry place at temperatures of +15 °C to +25 °C no direct sun radiation.

While transported within the usual transport times, the product may be exposed to temperatures from -30 °C to +35 °C.





# COSMO® CL-340.150

## Special cleaner

Storage life in unopened original packaging: 24 Months.

### Packaging

1 000 ml metal bottle

Other trading units on request.

### Accessories

COSMO® SP-870.100 - Pulp cleaning cloth

COSMO® SP-810.120 - Saving humidifier/safety dispenser

