



CLEANING & CARE SET UNIVERSAL

Examples for Application

- Cleaning of all surfaces in the field of wood, plastic and aluminium window, door and façade construction
- Production and assembly area of window construction
- Regular care of already assembled window, door and shutter profiles
- Streak-free cleaning of glass and high gloss surfaces, as well as office furniture and many plastic surfaces, also e.g. PC screens

Components

UNIVERSAL PROFILE CLEANER COSMO® CL-360.110	Detergent, surface-active cleaner for cleaning of all profile surfaces made of wood, plastic and aluminium windows, doors, and façades. Streak-free cleaning of glass and high gloss surfaces. Wood surfaces must be varnished or thick glazed.
SPECIAL CARE PEN COSMO® SP-880.110	For care and maintenance of sealings. It keeps the ductility, and in summer, it prevents the sealing from sticking on, while in winter, it prevents it from freezing on the profile.
FITTING OIL COSMO® SP-890.110	For care and maintenance of fitting and hinges. It preserves the necessary sliding characteristics of the moveable parts, and in this way, it avoids dry rubbing connected with running/eating into the metals and furthermore, it provides additional corrosion protection.
PROFI MICROFIBRE CLOTH	Special cleaning cloth with high number of meshes for professional cleaning of all profile surfaces in combination with UNIVERSAL PROFILE CLEANER and SPECIAL PROFILE CLEANER.

Instructions for use

The instructions for use of the individual components can be found in the corresponding Technical Data Sheets.

Important instructions

Our user instructions, processing guidelines, product- and performance data, and other technical statements are only general directives; they describe only the condition of our products (values, determination of values on the date of completion) and the performances do not represent a warranty in the sense of § 443 BGB. **Because of the wide variety of applications of the individual product and the relevant special conditions (e. g. processing parameters, material characteristics, etc.), it is up to the user to test it itself;** our free expert advice for application provided in speech, writing, and as test is nonbinding.

Please, also consider the Safety Data Sheet!

Storage

Store the hermetically closed original trading units in a dry place at temperatures of +15 °C to +25 °C no direct sun radiation.

While transported within the usual transport times, the product may be exposed to temperatures from -30 °C to +35 °C.

Storage life in unopened original packaging: 24 Months



Industrieverband
Klebstoffe e.V.



Weiss Chemie + Technik
GmbH & Co. KG
Hansastraße 2
D-35708 Haiger

Tel.: +49 (0) 2773 / 815 - 0
Fax: +49 (0) 2773 / 815 - 200
Email: ks@weiss-chemie.de
Web: www.weiss-chemie.de

made by weiss