



## Dispersion sealant

### Declaration of Performance

as per Annex III of the Regulation (EU) No. 305/2011

LE/DoP-Nr. WCTDS0001-02

1. Identification code of product type: COSMO® DS-420.301
2. Ident. No.: Batch number: see imprint on trading unit
3. Intended use: Dispersion sealant,  
Sealing compound on the basis of acrylate dispersion  
Jointing compound for façade elements for indoor and outdoor applications  
Type: F EXT-INT 12.5 P
4. Manufacturer: Weiss Chemie + Technik GmbH & Co. KG  
Hansastraße 2  
D-35708 Haiger
5. Authorised representative: --
6. System for assessment of permanent performance: 3 plus 3
7. Harmonised standard: EN 15651-1:2012
8. Notified authority: Ginger CEBTP (NB-No.: 0074), as notified test laboratory in the Conformity System 3, conducted the first test and issued the test and classification reports.
9. Declared performance: Conditioning: Storage A  
Carrier material: Anodised aluminium without primer  
Mortar M2 without primer

Essential characteristics	Performance	Harmonised technical specifications
Fire behaviour	Class E	1
Exposition of chemicals that are environmentally hazardous and/or hazardous to health	Rated	1
Watertightness and airtightness		
Resistance to flow	≤ 3 mm	1
Loss of volume	≤ 25 %	1
Tensile behaviour (i.e. elongation) after immersing in water (at +23 °C)	≥ 100 %	1
Durability	Passed	1

1 = EN 15651-1:2012

NF = No failure as per EN ISO 11600

10. The performance of the product mentioned above refers to the performance/s declared.

The above named manufacturer is solely responsible for the creation of the Declaration of Performance in conformity with regulation (EU) No. 305/2011.





## Dispersion sealant

Signed for the manufacturer and on behalf of the manufacturer by:

[Manufacturer's authorized representative]

Haiger, 09.05.2025

ppa. Dr. Oliver Flender  
Vice President Research & Development  
Adhesive Division



Industrieverband  
Klebstoffe e.V.