

**1-K PUR sealant****Declaration of Performance**

as per Annex III of the Regulation (EU) No. 305/2011

LE/DoP-Nr. WCTPU0001-02

- |    |  |  |
|----|--|--|
| 1. | Identification code of product type:               | COSMO® PU-110.161  |
| 2. | Ident. No.:  | Batch number: see imprint on trading unit  |
| 3. | Intended use:                                      | 1-Component PUR Sealant,<br>humidity-cross linking polyurethane<br><br>Jointing compound for façade elements for indoor and outdoor applications (suitable for the application in cold climatic zones)<br>Type: F EXT-INT-CC 25 LM<br><br>Jointing compound for pedestrian ways for indoor and outdoor applications (suitable for application in cold climatic zones)<br>Type: PW EXT-INT-CC 25 LM |
| 4. | Manufacturer:                                      | Weiss Chemie + Technik GmbH & Co. KG<br>Hansastraße 2<br>D-35708 Haiger  |
| 5. | Authorised representative:                         | --   |
| 6. | System for assessment of constancy of performance: | 3 plus 3   |
| 7. | Harmonised standard:                               | EN 15651-1:2017<br>EN 15651-4:2017   |
| 8. | Notified authority:                                | 4ward Testing Ltd, NB 2538, as a notified testing laboratory in Conformity System 3, conducted the first test and issued the test and classification reports.  |
| 9. | Declared performance:                              | Conditioning: Storage A<br>Carrier material: Mortar M1 with Primer COSMO® CL-310.130   |

Essential characteristics	Performance	Harmonised technical specifications
Fire behaviour	Class E	1, 2
Exposition of chemicals that are environmentally hazardous and/or hazardous to health	Rated	1, 2
Watertightness and airtightness		
Resistance to flow	≤ 3 mm	1
Loss of volume	≤ 10 %	1, 2
Tensile behaviour (i.e. elongation) under pretension after immersing in water	NF	1, 2
Tensile behaviour (i.e. secant module) for non-bearing joint sealants with low module (at -30 °C)	≤ 0.9 MPa	1, 2
Tensile behaviour (i.e. under pretension) for non-bearing joint sealants (at -30 °C)	NF	1, 2

Industrieverband  
Klebstoffe e.V.

Weiss Chemie + Technik  
GmbH & Co. KG  
Hansastraße 2  
D-35708 Haiger

Tel.: +49 (0) 2773 / 815 - 0  
Fax: +49 (0) 2773 / 815 - 200  
Email: [ks@weiss-chemie.de](mailto:ks@weiss-chemie.de)  
Web: [www.weiss-chemie.de](http://www.weiss-chemie.de)

made by weiss

**1-K PUR sealant**

Tearing strength	NF	2
Adhering/expansion behaviour under pretension after 28 days laid in water	NF	2
Adhering/expansion behaviour under pretension after 28 days laid in salt water	NF	2
Durability	Passed	1, 2

1 = EN 15651-1:2017

2 = EN 15651-4:2017

NF = No failure as per EN ISO 11600

10. The performance of the product mentioned above refers to the performance/s declared.

The above named manufacturer is solely responsible for the creation of the Declaration of Performance in conformity with regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer by:

[Manufacturer's authorized representative]

Haiger, 09.05.2025

ppa. Dr. Oliver Flender

Vice President Research & Development

Adhesive Division



Industrieverband  
Klebstoffe e.V.